

CXT brass cable glands



Gland Size (mm)	Thread Size	Cable Diameter (mm)	
		min	max
CXT-20/16	20	3.1	8.6
CXT-20s	20	6.1	11.6
CXT-20 20	20	6.5	13.9
CXT-25 25	25	11.1	19.9
CXT-32 32	32	17.0	26.2
CXT-40 40	40	22.0	32.1
CXT-50s	50	29.5	38.1
CXT-50 50	50	35.6	44.0
CXT-63s	63	42.2	49.9
CXT-63 63	63	48.3	54.9
CXT-75s	75	54.2	

Metric & PG IP68 Nylon Compression Glands



THREAD mm	HOLE SIZE mm	LENGTH OF THREAD mm	CABLE RANGE MIN-MAX Ø
M 12 x 1.5	12.0	8.0	3.0 - 6.5
M 16 x 1.5	16.0	10.0	5.0 - 10.0
M 16 x 1.5	16.0	15.0	5.0 - 10.0
M 20 x 1.5	20.0	10.0	6.0 - 12.0
M 20 x 1.5	20.0	15.0	6.0 - 12.0
M 20 x 1.5	20.0	10.0	10.0 - 14.0
M 20 x 1.5	20.0	15.0	10.0 - 14.0
M 25 x 1.5	25.0	10.0	13.0 - 18.0
M 25 x 1.5	25.0	15.0	13.0 - 18.0
M 32 x 1.5	32.0	18.0	16.0 - 25.0
M 40 x 1.5	40.0	18.0	22.0 - 32.0
M 50 x 1.5	50.0	18.0	30.0 - 38.0
M 63 x 1.5	63.0	18.0	34.0 - 44.0

The information contained within this data sheet is for guidance only.

Cable and gland sizes are nominal and may vary according to different manufacturer's tolerances.

Every possible effort is made to ensure that the Information contained in this data sheet is correct.

However, we reserve the right to change the information or specification at any time in the light of technical developments or revisions. References to or extracts from British Standards, current IEE regulations or other regulatory bodies should be verified with these organisations.

T 01582 665050 | F 01582 665060 | sales@premiercables.com | www.premiercables.com

WORLDWIDE CABLE SOLUTIONS