

9368_{eQ} LSF

9368_{eQ} LSZH



Generally, to Belden 9368



Application

Individually screened multi paired for computer, instrumentation and audio applications. The individually screened pairs reduce cross talk. Reduced losses are achieved through the use of 18AWG conductors making this cable ideal for long runs.

Construction

Conductor	Tinned copper
Inner Sheath	PP (Polypropylene)
Pairs	2
Screen	Individually Aluminium foil
Drain wire	Tinned copper
Sheath	LSF or LSZH (Low Smoke Zero Halogen)
Voltage	300v
Nominal O/D	9.6mm
Min Bending Radius	10 x O/D flexing
Weight	103kg/km
Temperature Rating	Fixed: -20°C to +70°C
Core Identification	Pair 1: Black / Red- numbered 1 Pair 2: Black / Red- numbered 2
Sheath colour	Grey

	Capacitance		Resistance	Max resistance of Conductor at 20°C
	pF/m	Conductor to Shield	MΩ.M	Ω/km
Conductor to Conductor	140	260	>200	<20

The information contained within this data sheet is for guidance only.

Cable and gland sizes are nominal and may vary according to different manufacturer's tolerances.

Every possible effort is made to ensure that the Information contained in this data sheet is correct.

However, we reserve the right to change the information or specification at any time in the light of technical developments or revisions.

References to or extracts from British Standards, current IEE regulations or other regulatory bodies should be verified with these organisations.

T 01582 665050 | F 01582 665060 | sales@premiercables.com | www.premiercables.com

WORLDWIDE CABLE SOLUTIONS