

# 8723<sub>eQ</sub> LSF

# 8723<sub>eQ</sub> LSZH



Generally, to Belden 8723, RS232, UL1581



## Application

22 AWG/ 7/0.254)

Individual screened pair Computer, Point of sale RS232 Cable

## Construction

Conductor	Class 2 stranded tinned copper conductor
Inner Sheath	Polyethylene
Pairs	2
Screen	Aluminium polyester foil
Drain Wire	Tinned copper
Sheath	LSF or LSZH (Low Smoke Zero Halogen)
Nominal OD	4.2mm
Nominal Weight	30kg/km
Voltage Rating	300V
Temperature Rating	Fixed: -20°C to +80°C

## Core Identification

Pair 1: Black / /Red

Pair 2: Green / White

Sheath colour Grey

This product is available in:

PE – Polyethylene Duct Grade

SWA – Steel Wire Armour for direct burial

Capacitance at 1kHz	Max Resistance of Conductor
pF/m	Ohms/km
114.8	65.3

*The information contained within this data sheet is for guidance only.*

*Cable and gland sizes are nominal and may vary according to different manufacturer's tolerances.*

*Every possible effort is made to ensure that the information contained in this data sheet is correct.*

*However, we reserve the right to change the information or specification at any time in the light of technical developments or revisions.*

*References to or extracts from British Standards, current IEE regulations or other regulatory bodies should be verified with these organisations.*

[sales@premiercables.com](mailto:sales@premiercables.com)

[www.premiercables.com](http://www.premiercables.com)

**WORLDWIDE CABLE SOLUTIONS**